

Quality Product CertificationSeparation and Filtration

This product has been found to be fit for use in accordance with NorGeoSpec 2012 System for the above given function.

Certificate no.:	NGS-50137
Date:	05.09.2018
Valid until:	04.09.2020
Manufacturer:	Tessilbrenta
Product:	HIPERTEX TB2
Product Type:	GTX-N
Raw material:	PP
Function:	Separation and Filtration

Issued by

Christian Recker, SINTEF project manager

Approved by

Arnstein Watn, Head of the Technical committee

NorGeoSpec

NorGeoSpec

NorGeoSpec

NorGeoSpec

The products are regularly audited and tested to verify that the characteristics fulfil the NorGeoSpec 2012 Rev.: 01/14.12.2016 requirements. Approved by the NorGeoSpec Technical committee: 05.09.2018



Certificate no.: NGS-50137

Quality Product CertificationSeparation and Filtration

Characteristic		Standard	Unit	Declared value	Max. tolerance	Certification value
Mass per unit area		EN ISO 9864	g/m²	135	± 14	122 - 149
Mechanical tests						
Tensile strength	MD	EN ISO 10319	kN/m	9.60	- 0.90	10.00
	CMD	EN ISO 10319	kN/m	12.50	- 1.20	10.00
Tensile strain at tensile strength	MD	EN ISO 10319	%	49.0	- 9.8	20.2
	CMD	EN ISO 10319	%	49.0	- 9.8	39.2
Static puncture test		EN ISO 12236	KN	1.700	- 0.170	1.530
Dynamic perforation resistance		EN ISO 13433	mm	30	6	36
Energy index		NorGeoSpec 2012	kN/m	2.1	0.0	2.1
Hydraulic tests						
Permeability normal to the plane without load		EN ISO 11058	m/s	0.070	- 0.021	0.049
Characteristic opening size		EN ISO 12956	μm	85	± 26	60 - 111
Durability (Declared value)						
Service life			years	<u>25</u>	<u></u> 50	<u> </u>

Quality Product Certification: Separation and Filtration Application profile: 2